

Hydraulic Passenger Lift Range

The data below only reflects our most common sizes and configurations (at a speed of 0.6m/s).

Further sizes and speeds are available so if you do not find what you are looking for, please ask.

Note: 2PSO= 2 Panels Side Opening, 6PCO= 6 Panels Centre Opening.

Load	Entrance Layout	Internal Shaft Dimensions		Car Size (at height of 2100mm)		Door Types	Doors Opening (at height of 2000mm)		Pit	Headroom
		Width (mm)	Depth (mm)	Width (mm)	Depth (mm)		Width (mm)	Depth (mm)		
180/2	Single	1250	900	800	700	Manual/Hinged	700	1200	3400	
225/3	Single	1000	1250	850	825	Manual/Hinged	700	1200	3400	
225/3	Single	1200	1090	800	850	Manual/Hinged	700	1200	3400	
300/4	Single	1400	1250	900	950	2PSO Automatic	700	1200	3400	
300/4	Through (180°)	1500	1400	850	950	2PSO Automatic	700	1200	3400	
450/6	Single	1500	1460	1000	1200	2PSO Automatic	800	1200	3400	
450/6	Through (180°)	1500	1540	1000	1200	2PSO Automatic	800	1200	3400	
630/8	Single	1650	1650	1100	1400	2PSO Automatic	800/900	1200	3400	
630/8	Through (180°)	1650	1790	1100	1400	2PSO Automatic	800/900	1200	3400	
630/8	Adjacent (90°)	1660	1700	1100	1400	2PSO Automatic	800	1200	3400	
750/10	Single	1650	1860	1100	1600	2PSO Automatic	900	1250	3650	
750/10	Through (180°)	1650	1960	1100	1600	2PSO Automatic	900	1250	3650	
1000/13	Single	1800	2400	1100	2100	2PSO Automatic	900	1250	3650	
1000/13	Through (180°)	1800	2460	1100	2100	2PSO Automatic	900	1250	3650	
1250/16	Single	1900	2600	1200	2300	2PSO Automatic	1000	1250	3650	
1250/16	Through (180°)	1900	2660	1200	2300	2PSO Automatic	1000	1250	3650	
1300/18	Single	1900	2630	1250	2300	2PSO Automatic	1000	1250	3650	
1300/18	Through (180°)	1900	2690	1250	2300	2PSO Automatic	1000	1250	3650	
1500/20	Single	1950	2700	1300	2400	2PSO Automatic	1100	1250	3650	
1500/20	Through (180°)	1950	2790	1300	2400	2PSO Automatic	1100	1250	3650	
1800/24	Single	2300	2700	1450	2400	2PSO Automatic	1100	1250	3650	
1800/24	Through (180°)	2300	2790	1450	2400	2PSO Automatic	1100	1250	3650	
2000/26	Single	2450	3000	1500	2700	2PSO Automatic	1200	1250	3650	
2000/26	Through (180°)	2450	3090	1500	2700	2PSO Automatic	1200	1250	3650	
2500/33	Single	2450	3550	1500	3250	2PSO Automatic	1200	1250	3650	
2500/33	Through (180°)	2450	3640	1500	3250	2PSO Automatic	1200	1250	3650	
3000/40	Single	2650	2625	1700	3250	2PSO Automatic	1200	1250	3650	
3000/40	Through (180°)	2650	3710	1700	3250	2PSO Automatic	1200	1250	3650	

Goods – Passenger Systems (to EN81 Part 2 Table 1:1A)

4240	Single	3500	6450	2600	6000	6PCO Automatic	2500	1300	3500
4240	Through (180°)	3500	6450	2600	6000	6PCO Automatic	2500	1300	3500
4600	Single	3600	6450	2700	6000	6PCO Automatic	2600	1300	3500
4600	Through (180°)	3600	6450	2700	6000	6PCO Automatic	2600	1300	3500

Note – all details are correct at time of compilation, however all data maybe subject to change without prior notice at any time. This data is merely a selection of that available, most non-standard variations are easily possible, so please contact us with your specific site conditions.